


### Key Features

- IGBT inverter technology
- Suitable for welding cellulosic electrode
- Digital ammeter
- Anti-stick, Arc-force, Hot start, Lift TIG
- Advanced control technology
- Excellent weld characteristics
- Auto-compensation for voltage fluctuation
- Remote control option
- VRD option
- Generator friendly\*\*

**NOW WITH  
CELLULOSIC  
CAPABILITY**



### Technical Data

Input Voltage	AC 400V - 50/60 Hz
I <sub>eff</sub> (A)	19.6
Input Power (kVA)	18.2
Current Range (A)	30 - 400
Duty Cycle @ 40°C	400A @ 60%
No-Load Voltage (V)	79 (9V - VRD)
Efficiency (%)	85
Power Factor	0.95
Protection/Insulation Class	IP21S/F
Dimensions (LxWxH mm)	618 x 330 x 441
Weight (Kg)	20


The Jasic Arc 400 MMA welding inverter is equipped with the latest IGBT technology and digital meters.

This technologically advanced inverter is extremely user-friendly and offers reliable and consistent arc performance. The Arc 400 also offers lift TIG functionality making it an ideal choice for industrial applications.

The VRD (Voltage Reduction Device) option is an added safety function that reduces the open circuit voltage of the welding power source which is used in the MMA/Stick welding process when welding is not taking place to a safe voltage low voltage (9V). The VRD function does not affect the welding performance of the machine.

### Options Accessories

Part Number	Description
WCS50-3	Welding Cable Set 3m
WP26V-12-2DL	WP26V 4m TIG Torch
WP26V-25-2D	WP26V 8m TIG Torch
JRC-25	Remote 25m



- |                             |                                   |
|-----------------------------|-----------------------------------|
| 1 Digital Display           | 6 Arc Force Control               |
| 2 Warning Indicator         | 7 Selection Switch = Local Remote |
| 3 Overcurrent LED/Indicator | 8 Process Selection Switch        |
| 4 VRD Indicator             | 9 Cellulosic Function Switch      |
| 5 Hot Start Control         | 10 Current Control                |